



**Jinlong Chemical Fiber**  
金隆化纤



<https://shop2473j16o8f461.1688.com>



地址：山东省海阳市邢家工业园香江街8号

Address: No. 8 Xiangjiang Street, Xingjia Industrial Park, Haiyang City, Shandong Province

专业生产高温丝、低温丝、阻燃丝、PP系列等假发化纤丝  
Specializing in the production of high-temperature silk, low-temperature silk,  
flame-retardant silk, PP series and other synthetic fibers for wigs

**金隆化纤制品有限公司**  
JINLONG CHEMICAL FIBER CO.LTD





Jinlong Chemical Fiber  
金隆化纤

# CONTENTS

## 目录

### 01

#### 公司简介

COMPANY PROFILE

### 02

#### 产品介绍

PRODUCT INTRODUCTION

- |   |  |
|---|--|
| 02- HA(高温柔软丝)<br>HA (high Gentle Soft Silk)             | 10- MZ (低温阻燃发丝)<br>MZ (low Temperature Flame Retardant Hair) |
| 03- BI(蛋白丝)<br>BI (egg White Silk)                      | 10- PPZR(PP阻燃丝)<br>PPZR (PP Flame Retardant Filament)        |
| 04- HYII (高温全哑光)<br>HYii (high Temperature Full Matte)  | 11- LM (夜光丝)<br>LM (luminous Silk)                           |
| 05- HY (高温哑光丝)<br>HY (high Temperature Matte Silk)      | 11- BG (光变丝)<br>BG (light Transformed Silk)                  |
| 05- H丝 (高温有光丝)<br>H Wire (high-temperature Glossy Wire) | 12- PP<br>PP   |
| 06- WB (中温丝)<br>WB (medium Temperature Wire)            | 13- DR成型丝<br>DR Forming Wire                                 |
| 07- GS (中温丝)<br>GS (medium Temperature Wire)            | 13- DT成型丝<br>DT Forming Yarn                                 |
| 08- MT (低温丝)<br>MT (low Temperature Wire)               | 13- QGB成型丝<br>QGB Forming Yarn                               |
| 09- MB (水烫丝)<br>MB (water Iron)                         | 13- QGD成型丝<br>QGD Forming Yarn                               |



## COMPANY PROFILE

### 公司简介

金隆化纤制品有限公司成立于2016年，坐落于美丽的滨海城市山东·海阳。公司拥有四十多套生产线，采用日本、韩国技术，主要生产高温丝、柔软丝、低温丝、阻燃丝、PP系列等假发化纤丝，颜色上百种，产品易定型、手感好、易梳理，是发制品行业的专业供应商，年产量达8000吨以上，现已与国内外多家发制品公司合作，公司本着品质优良、诚信经营、信誉至上的原则与各界朋友共谋发展、共创辉煌!

Jinlong Chemical Fiber Products Co., Ltd. was established in 2016 and is located in the beautiful coastal city of Haiyang, Shandong. The company has more than 40 production lines and adopts Japanese and Korean technology. It mainly produces high-temperature silk, soft silk, low-temperature silk, flame-retardant silk, PP series and other wig like fibers in hundreds of colors. The products are easy to shape, have a good hand feel, and are easy to comb. It is a professional supplier in the hair industry with an annual output of over 8000 tons. The company has cooperated with many hair product companies at home and abroad. Based on the principles of excellent quality, honest management, and reputation first, the company seeks common development and creates brilliance with friends from all walks of life!





Jinlong Chemical Fiber  
金隆化纤

## HA (HIGH GENTLE SOFT SILK) HA(高温柔软丝)

HA(高温柔软丝): 手感柔软度更胜一筹 适用于做高端假发套、配件等产品。

耐温度: 180°C

定型温度: 110°C 40分钟

HA (High Gentle Soft Silk): It has a softer hand feel and is suitable for making high-end wig covers, accessories, and other products.

Temperature resistance: 180 °C

Setting temperature: 110 °C for 40 minutes



Jinlong Chemical Fiber  
金隆化纤

## BI (EGG WHITE SILK) BI(蛋白丝)

BI(蛋白丝): 手感超软超滑, 适用于做高端曲发, 可混于人发一起使用。

夹板温度: 130°C

定型温度: 95±5°C 40分钟

BI (egg white silk): It has a super soft and smooth feel, suitable for making high-end curved hair, and can be mixed with human hair for use.

Clamping plate temperature: 130 °C

Molding temperature: 95 ± 5 °C for 40 minutes







Jinlong Chemical Fiber  
金隆化纤



## HYII (HIGH TEMPERATURE FULL MATTE) HYII (高温全哑光)

HYII (高温全哑光)：人发光泽，手感顺滑，适用于做头套、配件等产品。

夹板温度：180℃

定型温度：110℃ 40分钟

HYII (High Temperature Full Matte): With a glossy finish and a smooth feel, it is suitable for making headgear, accessories, and other products.

Clamping plate temperature: 180 °C

Setting temperature: 110 °C for 40 minutes

## HY (HIGH TEMPERATURE MATTE SILK) HY (高温哑光丝)



发丝特点：手感光滑垂感好，哑光度高，适用于头套、配件等产品。

夹板温度：180℃

定型温度：110℃ 40分钟

Hair characteristics: Smooth texture, good drape, high matte finish, suitable for headgear, accessories and other products.

Clamping plate temperature: 180 °C

Setting temperature: 110 °C for 40 minutes

## H WIRE (HIGH-TEMPERATURE GLOSSY WIRE) H丝 (高温有光丝)

发丝特点：色泽鲜明 适用于头套、发帘等产品。

夹板温度: 180℃

定型温度: 110℃ 40分钟

Hair characteristics: Bright color suitable for products such as hair covers and hair curtains.

Clamping plate temperature: 180℃

Setting temperature: 110 °C for 40 minutes







Jinlong Chemical Fiber  
金隆化纤

## WB (MEDIUM TEMPERATURE WIRE) WB (中温丝)



发丝特点：手感柔软 适合EZ等辫子产品

夹板温度：130°C

定型温度：95±5度 40分钟

Hair characteristics: Soft to the touch, suitable for braided products such as EZ

Clamping plate temperature: 130 °C

Setting temperature: 95 ± 5 degrees Celsius for 40 minutes



Jinlong Chemical Fiber  
金隆化纤

## GS (MEDIUM TEMPERATURE WIRE) GS (中温丝)



发丝特点：适合做大小卷产量，YK效果蓬松。75度热水里  
可变直

夹板温度：130°C

定型温度：95±5度 40分钟

Hair characteristics: Suitable for producing large and small rolls, YK effect is fluffy.

Variable straightness in 75 degree hot water

Clamping plate temperature: 130 °C

Setting temperature: 95 ± 5 degrees Celsius for 40 minutes





Jinlong Chemical Fiber  
金隆化纤

## MT (LOW TEMPERATURE WIRE) MT (低温丝)



发丝特点：色泽明亮，适合做钩针发等小曲发类的产品

夹板温度:110℃

定型温度: 85±5度 40分钟

Hair characteristics: Bright color, suitable for making crochet hair and other small curly hair products

Clamping plate temperature: 110 °C

Setting temperature: 85 ± 5 degrees Celsius for 40 minutes



Jinlong Chemical Fiber  
金隆化纤

## MB (WATER IRON) MB (水烫丝)



发丝特点：用热水烫收缩比可以达到50%-60%

夹板温度:110℃

定型温度: 85±5度 40分钟

Hair characteristics: the shrinkage ratio can reach 50%-60% with hot water

Splint temperature: 110℃

Setting temperature: 85±5℃ for 40 minutes





Jinlong Chemical Fiber  
金隆化纤

## MZ (LOW TEMPERATURE FLAME RETARDANT HAIR) MZ (低温阻燃发丝)

发丝特点：色泽鲜明，适合钩针发等曲发类产品

夹板温度:110℃

定型温度: 85±5度 40分钟

Hair characteristics: Bright color, suitable for  
crochet hair and other curly hair products

Clamping plate temperature: 110 °C

Setting temperature: 85 ± 5 degrees Celsius for 40  
minutes



## PPZR (PP FLAME RETARDANT FILAMENT) PPZR(PP阻燃丝)

发丝特点：蓬松度极佳，适用于做辫子类产品

夹板温度: 90℃

定型温度: 75±5℃ 40分钟

Hair characteristics: Excellent fluffiness, suitable  
for making braided products

Clamping plate temperature: 90℃

Molding temperature: 75 ± 5 °C for 40 minutes



Jinlong Chemical Fiber  
金隆化纤

## LM (LUMINOUS SILK) LM (夜光丝)

发丝特点：白天原色，夜晚黄绿光。

Hair characteristics: natural color during the day,  
yellow green light at night.



## BG (LIGHT TRANSFORMED SILK) BG (光变丝)

发丝特点：可根据紫外线的强弱变换深浅

Hair characteristics: The depth can be changed  
according to the strength of ultraviolet rays







Jinlong Chemical Fiber  
金隆化纤

## PP

PP 适用于各种辫子，同系列还有R丝（软丝）、M丝（蓬松）K丝（垂感丝）

PP is suitable for various braids, and the same series also includes R silk (soft silk), M silk (fluffy), K silk (drooping silk)



Jinlong Chemical Fiber  
金隆化纤



DR成型丝 耐温：80度

DT成型丝 耐温：80度

DR Forming Wire Temperature resistance: 80 degrees

DT Forming Yarn Temperature resistance: 80 degrees

QGB成型丝 耐温：80度

QGD成型丝 耐温：80度

QGB Forming Yarn Temperature resistance: 80 degrees

QGD Forming Yarn Temperature resistance: 80 degrees

